

chat.fetchMessages

This method allows an app to fetch specific messages from a conversation.

The method endpoint is <https://api.flock.co/v1/chat.fetchMessages> and follows the [method calling conventions](#).

Your app provides a list of message uids to fetch, and Flock will, in response, return a list of [Message](#) objects.

Parameters

Name	Type	Required	Description
token	String	Yes	Token of the user on whose behalf the message is being sent
chat	String	Yes	Identifier for user or group for which messages are to be fetched
uids	Array	Yes	A comma separated list of message uids (max length: 25). If a message doesn't exist for any uid, it is silently skipped. Example: ["fd4877b719b1", "59e2da001af2"]

Response

A list of [Message](#) objects.

```
[ { "from": "u:1e6429de-16b7-48b3-acc0-c2d7ec5ad195",  
  "to": "u:cfc76545-3400-4864-892a-513a9f4ae409",  
  "uid": "fd4877b719b1",  
  "text": "Hello" },  
  { "from": "u:cfc76545-3400-4864-892a-513a9f4ae409",  
    "to": "u:1e6429de-16b7-48b3-acc0-c2d7ec5ad195",  
    "uid": "59e2da001af2",  
    "text": "Hello again" } ]
```

Errors

Error Code	HTTP Status	Description	Additional Parameters
UnknownChat	400	The group or userId provided in chat is not known.	